

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Product name:** BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

**Product code:** PD0950

**Synonyms:** PD0950

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** Water based carpet and fabric cleaner.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** BRIGHT CHEM  
UNIT B8  
GROVE PARK SPRINGVALE ROAD  
GRIMETHORPE  
BARNESLEY  
S72 7BF  
UK GB & NI  
**Tel:** +44(0)7958295939  
**EMAIL:** info@brightchem.co.uk

**1.4. Emergency telephone number**

**Emergency tel:** +44(0)7958295939  
(office hours only)

**Section 2: Hazards identification****2.1. Classification of the substance or mixture**

**Classification under CLP:** Eye Dam. 1: H318

**Most important adverse effects:** Causes serious eye damage.

**2.2. Label elements****Label elements:**

**Hazard statements:** H318: Causes serious eye damage.

**Hazard pictograms:** GHS05: Corrosion



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

# SAFETY DATA SHEET

BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P315: Get immediate medical advice/attention.

**Haz. ingredients (label):** Contains: HYDROGEN PEROXIDE

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

HYDROGEN PEROXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-765-0	7722-84-1	-	Acute Tox. 4: H302; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H335; Acute Tox. 4: H332	1-10%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

[cont...]

# SAFETY DATA SHEET

BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

Page: 3

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

[cont...]

# SAFETY DATA SHEET

BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

Page: 4

**Hazardous ingredients:**

**HYDROGEN PEROXIDE**

**Workplace exposure limits:**

**Respirable dust:**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1.4 mg/m <sup>3</sup>	2.8 mg/m <sup>3</sup>	-	-

## DNEL/PNEC Values

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Barely perceptible odour

**Evaporation rate:** Slow

**Oxidising:** Oxidising (by EC criteria)

**Solubility in water:** Miscible in all proportions

**Boiling point/range°C:** 100

**Melting point/range°C:** 0

**Flash point°C:** >93

**Relative density:** 1.02

**pH:** 4.5

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

# SAFETY DATA SHEET

BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

Page: 5

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

#### HYDROGEN PEROXIDE

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>225	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

Hazardous ingredients:

#### HYDROGEN PEROXIDE

Daphnia magna	48H EC50	7.7	mg/l
RAINBOW TROUT	96H LC50	38.5	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

[cont...]

# SAFETY DATA SHEET

BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

Page: 6

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

## 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 20 01 30

**Disposal of packaging:** Clean with water. May be reused following decontamination. Recycle container where permitted. Disposal of waste containers must be done in accordance with local and / or national regulations.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.

[cont...]

## **SAFETY DATA SHEET**

BRIGHT CHEM HIGH POWER VLM PRE-SPRAY

**Page: 7**

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.