

BRIGHT CHEM SOLVENT SPOTTER -STAIN REMOVER

Page: 1

Compilation date: 09/01/2024

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BRIGHT CHEM SOLVENT SPOTTER -STAIN REMOVER

Product code: PD0927

Synonyms: PD0927

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Water based carpet and fabric cleaner.

1.3. Details of the supplier of the safety data sheet

Company name: BRIGHT CHEM UNIT B8 GROVE PARK SPRINGVALE ROAD GRIMETHORPE BARNSLEY S72 7BF UK GB & NI Tel: +44(0)7958295939 Email: info@brightchem.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0)7958295939 (office hours only)

Section 2: Hazards identification

2.1. Classification of the subst	ance or mixture
Classification under CLP:	STOT SE 3: H336; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin
	Irrit. 2: H315; -: EUH066
Most important adverse effects:	Repeated exposure may cause skin dryness or cracking. Flammable liquid and vapour.
	Causes skin irritation. Causes serious eye irritation. May cause drowsiness or
	dizziness. Harmful to aquatic life with long lasting effects.
2.2. Label elements	

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

		Page:	2
	H336: May cause drowsiness or dizziness.		
	H412: Harmful to aquatic life with long lasting effects.		
Hazard pictograms:	GHS02: Flame		
	GHS07: Exclamation mark		
Signal words:	Warning		
Precautionary statements:	P102: Keep out of reach of children.		
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition		
	sources. No smoking.		
	P280: Wear protective gloves/protective clothing/eye protection/face protection.		
	P243: Take action to prevent static discharges.		
	P242: Use non-sparking tools.		
	P261: Avoid breathing vapours.		
	P302+P352: IF ON SKIN: Wash with plenty of water.		
	P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.		
	Rinse skin with water .		
	P362+P364: Take off contaminated clothing and wash it before reuse.		
	P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for		
	breathing.		
	P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting		
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove		
	contact lenses, if present and easy to do. Continue rinsing.		
Haz. ingredients (label):	Contains: HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS; N-BUTYL		
	ACETATE; PROPAN-2-OL		
2.3. Other hazards			

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

	AS PBT / WE	L CLP Classificati	ion Percent
--	-------------	--------------------	-------------

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

				Page
926-141-6	64742-47-8	-	Asp. Tox. 1: H304; -: EUH066	30-50%
N-BUTYL ACETA	TE			
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
PROPAN-2-OL - F	REACH regis	ered number(s): 01-2119457558-2	5	
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%
2-BUTOXY ETHA	NOL - REAC	H registered number(s): 01-211947	5108-36-XXXX	
203-905-0	111-76-2	-	Acute Tox. 3: H331; Acute Tox. 4: H312; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Acute Tox. 4: H302	1-10%
HYDROCARBON (s): 01-211947551		ALKANES, CYCLICS, <5% N-HEX/	ANE, <0.1% BENZENE - REACH registered number	r
265-151-9	64742-49-0	-	Flam. Liq. 2: H225; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315	1-10%
tion 4: First aid	maasuras			
	measures			
1. Description of	first aid mea	sures		
Sk	kin contact:	Remove all contaminated clothes a	and footwear immediately unless stuck to skin. Was	h
		immediately with plenty of soap an	nd water.	
E	ye contact:	Bathe the eye with running water for	or 15 minutes. Consult a doctor.	
	Ingestion:	Wash out mouth with water. Consu	ult a doctor.	
	Inhalation:	Remove casualty from exposure e	nsuring one's own safety whilst doing so. Consult a	
		doctor.		
2. Most important	t symptoms	and effects, both acute and delay	yed	
Sk	kin contact:	There may be irritation and rednes	ss at the site of contact.	
E	ye contact:	There may be irritation and rednes	ss. The eyes may water profusely.	
	Ingestion:	There may be soreness and redne	ess of the mouth and throat.	
	Inhalation:	There may be irritation of the throa	at with a feeling of tightness in the chest. Exposure n	nay
		cause coughing or wheezing.		
Delayed / immedi	ate effects:	Immediate effects can be expected	d after short-term exposure.	
3. Indication of a	ny immediat	e medical attention and special tr	reatment needed	
nmediate / special	I treatment:	Eye bathing equipment should be	available on the premises.	
tion 5: Fire-fight	ing measu	es		
1. Extinguishing	media			
Fytinguish	ning media.	Alcohol resistant foam Water opro	ay. Carbon dioxide. Dry chemical powder. Use water	
Extinguisi	my meula.	Alconor resistant loant. Water Spla	ay. Carbon dionide. Dry chemical powder. Ose Waler	

spray to cool containers.

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Ventilate area well. Avoid sparks, flames, smoking and any other heat source. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Leaking material will evaporate leaving no residues.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

Respirable dust:

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200 mg/cm3	-	-	-

N-BUTYL ACETATE

UK	724 mg/m3	966 mg/m3	-	-

PROPAN-2-OL

UK 400 ppm 500 ppm - -

2-BUTOXY ETHANOL

	UK	25ppm (Sk)	50ppm (Sk)	-	-
--	----	------------	------------	---	---

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

UK	1100 mg/m3	2200 mg/m3	-	-	

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

F

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Colourless	
Odour:	Characteristic odour	
Evaporation rate:	Moderate	
Oxidising:	No data available.	
Solubility in water:	Slightly soluble	
Viscosity:	No data available.	
Boiling point/range°C:	>35 Melting point/range°C:	No data available.
Flammability limits %: lower:	2 upper:	14
Flash point°C:	25	

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

Page: 6 Part.coeff. n-octanol/water: No data available. Autoflammability°C: >230 Vapour pressure: No data available. Relative density: 0.81 pH: Not applicable. VOC g/l: 810 9.2. Other information Other information: No data available. Section 10: Stability and reactivity 10.1. Reactivity Reactivity: Stable under recommended transport or storage conditions. 10.2. Chemical stability Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/kg

N-BUTYL ACETATE

ORL RAT LD50 10768 mg/kg

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

Page: 7

PROPAN-2-OL

ORAL	RAT	LD50	4700	mg/kg
ORAL	RBT	LD50	>2000	mg/kg
VAPOURS	RAT	4H LC50	46.5	mg/l

2-BUTOXY ETHANOL

ORL RAT LD50	1200	mg/kg
--------------	------	-------

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

DERMAL	RBT	LD50	3350	mg/kg
ORAL	RAT	LD50	16750	mg/kg
VAPOURS	RAT	4H LC50	259	g/l

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-C14, ISOALKANES, LOW AROMATICS

Daphnia magna	48H EC50	>250	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

PROPAN-2-OL

Daphnia magna	48H EC50	>100	mg/l
FISH	48H EC50	>100	mg/l

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

Page: 8

2-BUTOXY ETHANOL RAINBOW TROUT (Oncorhynchus mykiss) 96H LC50 1474 mg/l HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE Daphnia magna 48H EC50 17.06 mg/l RAINBOW TROUT (Oncorhynchus mykiss) 96H LC50 9.766 mg/l 12.2. Persistence and degradability Persistence and degradability: Biodegradable. 12.3. Bioaccumulative potential Bioaccumulative potential: No bioaccumulation potential. 12.4. Mobility in soil Mobility: Readily absorbed into soil. 12.5. Results of PBT and vPvB assessment PBT identification: This product is not identified as a PBT/vPvB substance. 12.6. Other adverse effects Other adverse effects: Negligible ecotoxicity. Section 13: Disposal considerations 13.1. Waste treatment methods Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Recovery operations: Solvent reclamation/regeneration. Waste code number: 20 01 13 Disposal of packaging: Return to supplier. May be reused following decontamination. Dispose of as normal industrial waste. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Section 14: Transport information 14.1. UN number UN number: UN1993 14.2. UN proper shipping name Shipping name: FLAMMABLE LIQUID, N.O.S. 14.3. Transport hazard class(es) Transport class: 3

BRIGHT CHEM SOLVENT SPOTTER - STAIN REMOVER

Marine pollutant: No

Page: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H225: Highly flammable liquid and vapour.
	H226: Flammable liquid and vapour.
	H302: Harmful if swallowed.
	H304: May be fatal if swallowed and enters airways.
	H312: Harmful in contact with skin.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H331: Toxic if inhaled.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.